



# HEAVY-DUTY 3/4" AND 7/16" IMPACT WRENCHES

## 9075-20

- 3/4" SQUARE DRIVE WITH FRICTION RING AND THROUGH HOLE SOCKET RETENTION



**380  
FT.-LBS.  
OF TORQUE!**

### AVAILABLE CORDLESS

SEE PAGES 13, 24,  
AND 28  
FOR CORDLESS  
IMPACT WRENCHS

## 9092-20

- 7/16" HEX QUICK-CHANGE DUAL BALL BIT HOLDER
- 10' QUIK-LOK CORD



**315  
FT.-LBS.  
OF TORQUE!**

### FULL POWER IN REVERSE BEST POWER TO WEIGHT RATIO

- New Mechanism Delivers Higher Torque And Smoother Operation
- Metal Housing
- 7.0 Amp Milwaukee Built Motor
- Soft Grip Handle
- Ergonomically Balanced Center Grip

### 9075-20 FEATURES:

- 3/4" Square Drive With Friction Ring and Through Hole Rocket Retention
- Forward/Reverse Rocker Switch (AC/DC) Is Ideal When Frequent Reversing Is Necessary

### 9092-20 FEATURES:

- 7/16" Hex Quick-Change Dual Ball Bit Holder
- Forward/Reverse Lever
- Hanger Bracket w/Solid Steel Ring for hanging on belts, climbing pegs and for lifting with a rope and clasp.
- Variable Speed Trigger with Speed Setting Dial



## SPECIFICATIONS

CAT. NO.	VOLTS	AMPS	IMPACTS PER MINUTE	NO LOAD RPM	TORQUE FT.-LBS.	LENGTH INCHES	NET WGT. LBS.	SHIP WGT. LBS.
9075-20	120 AC/DC	7.0	2500	1,750	380	11-5/8	6.2	8.0
9092-20	120 AC	7.0	1000-2600	600-1,800	315	12-1/4	6.5	7.8

STANDARD EQUIPMENT: FOR 9075-20 – Tool and 8' 2-Wire Fixed Cord. FOR 9092-20 – Tool and Quik-Lok® Cord 48-76-5010.

## ACCESSORIES

### 1/2" SQUARE DRIVE HEX SOCKETS



Standard equipment for 9072-22 Kit.

- 49-66-3080 1/2" 49-66-3110 11/16"
- 49-66-3090 9/16" 49-66-3120 3/4"
- 49-66-3100 5/8" 49-66-3130 13/16"

### 5" LENGTH 1/2" SQUARE-DRIVE EXTENSION



- 48-95-5000 Adapts to 1/2" Square Drive. Provides 5" additional length where required for use with sockets.

### 1/2" SQUARE DRIVE UNIVERSAL JOINT



- 48-03-0500 Fits 1/2" Square Drive. Use with Hex Sockets to reach difficult places at various angles... also allows clearance around obstructions.

### 1/2" SQUARE DRIVE TO 7/16" HEX QUICK-CHANGE ADAPTER



- 48-66-0061 Use with 7/16" hex shank auger bits, selffeed bits or other 7/16" hex shank accessories which have ball-retainer grooves.

### RETAINING RINGS FOR 3/4" SQUARE ANVILS

- 44-86-0282 1-7/16" ID (use with 1-1/2" hub sockets)
- 44-86-0285 1-5/8" ID (use with 1-3/4" hub sockets)

### ROUND END DETENT KIT

- 49-17-0410 Use with 9066-6, 9068, 9070-20, 9072-20 and 9075-20. For quick socket changes.

### FLAT END DETENT KIT

- 49-17-0405 For 9066-6, 9068, 9070-20, 9072-20 and 9075-20. Replaces standard round detent pin on 9066-6, 9068. Socket will not slip off unless detent pin is pressed in. Below Serial No. 656-38701, Use 49-17-0400 Positive Detent Kit

### 5/8" HEX QUICK-CHANGE CONVERSION KIT



- 14-46-9095 Completely assembled, easily converts 7/16" front end to 5/8" hex.

### CHUCK ADAPTOR



- 48-66-0065 For 9092-20 and 9099-20. Adds versatility by enabling these tools to drill small holes (1/2" diameter max.) with jobber bits in steel, wood and plastic; or with carbide tipped bits to drill mortar, brick, etc. (NOT for use with any accessory that results in continuous impacting.)

### GREASE

- 49-08-7655 Type "Z" grease. For 9070-20, 9071-20, 9072-20.
- 49-08-4220 Type "J" grease. For 9075-20.