

## COMPLETE PRODUCT GUIDE





## **Applications**

	Fuel-P	owered	Cordle	ss Tool	S	Pneum	natic To	ols							
Application	30° Li-ion Framing CF325XP	16ga Angled Li-ion Flnish IM250ALi	16ga Straight Li-ion Finish IM250SLi	18ga Brad IM200Li	16ga Standard Crown Stapler	Power Framer <sup>тм</sup> PF350-S	50th Anniversary Framing Nailer	Positive Placement® Metal Connector Nailer PF250S-PP	Positive Placement® Metal Connector Nailer PF150S-PP	16ga Angled Trim T250A-F16	16ga Straight Trim T250S-F16	18ga Brad T200-F18	Insulation Sheathing Stapler S200-W16	Framing Stapler S200-S16	CapStapler CS150
Framing												-			
Exterior Walls	•					•	•								
Interior Walls	•					•	•								
Rafters	•					•	•								
Joists	•					•	•								
Metal Hardware								•	•						
Headers	•					•	•								
Blocking	•					•	•								
Bridging	•					•	•							•	
Floor Decks	•					•	•								
Roof Decks	•					•	•							•	
Punchout	•					•	•								
Assembly/Sheathing															
Plywood	•					•	•						•	•	
Gypsum Wallboard													•		
Soft Wall													•	•	
Polysterene													•		
Lathing													•	•	
Soffits	•			•	•									•	
Fascias	•			•	•									•	
Trim/Finish															
Bead Paneling		•	•	•						•	•	•			
Baseboards		•	•	•						•	•	•			
Crown Molding		•	٠	•						•	•	•			
Cap and Shoe		•	•	•						•	•	•			
Door and Window Jambs		•	٠	•						•	•	•			
Door and Window Casings		•	•	•						•	•	•			
Chair Rail Molding		•	٠	•						٠	•	•			
Roofing															
Roofing Felt													٠		•
Asphalt/Fiberglass Shingles													•		
Cedar Shingles	•					٠	•								
Siding/Exterior															
Housewrap													•		•
Wood	•					•	•								
Cedar and redwood	•					•	•								
Hardboard	•					•	•								
Vinyl														Δ	
Exterior Fences	•					•	•							•	
Recreational Decks	•					•	•								
Remodeling	•	•	•	•	•										
$\circ$ Tool without shingle guide; $\Delta$ Wit	h accessory f	for vinyl sidin	Ig												
Always check with local building code		r compliance													

Always check with local building codes for fastener compliance



#### **Cordless Li-ion Framing Nailer**



15% More Power to drive nails flush Works in All Seasons down to 14°F 9,000 shots per battery charge

#### Fuel + Nail Combo Packs:

Our industry leading fuel and nails in one convenient package. Note: 1,000 count cartons contain 1 fuel cell. 3,000 count cartons contain 3 fuel cells.

0







		Cord	dless Framing F	uel + Nail Com	bo Packs	
	Part #	Length	Diameter	Shank	Finish	#/Box
	650564	2"	.113"	Ring	HDG Plus	1,000
	650526	2 3/8"	.113"	Ring	HDG Plus	1,000
	650522	2 3/8"	.113"	Smooth	Brite	1,000
	650523	2 3/8"	.113"	Ring	Brite	1,000
	650565	2 3/8"	.113"	Ring	Brite	3,000
	650527	3"	.120"	Ring	*HDG Plus	1,000
	650563	3"	.120"	Smooth	*HDG Plus	1,000
Bui	650524	3"	.120"	Smooth	*Brite	1,000
POWER BOOST COATING	650631	3"	.120"	Smooth	*Brite	3,000
OST (	650525	3"	.131"	Smooth	*Brite	1,000
00	650566	3"	.131"	Smooth	*Brite	3,000
owe	650535	3 1/4"	.131"	Smooth	*Brite	3,000
۲	650630	3 1/4"	.131"	Smooth	*Brite	1,000
	650611	3 1/4"	.131"	Smooth	*HDG Plus	1,000

YEAR Full

WARRANTY

Designed and Assembled in the U.S.A.

Visit paslode.com for product reviews, downloads, videos and more Paslode® is a registered trademark of Illinois Tool Works Inc. ©2016

## **Cordless Framing**

T	ool Specifications
Model	CF325XP
Part #	905600
Weight	7.20lbs w/battery
Nail Capacity	1 strip (48 nails)
Nail Range	2" - 3 ¼", .113131
Nail Type	30° Paslode RounDrive® Full Head 30° Paslode Clipped Head
Fuel Type	All-Season Fuel (part# 816008)
Nails per Fuel Cell	Approx. 1,200
Battery	Li-ion battery (part# 902654) and charger (part# 902667)
Battery Life	9,000 nails per charge
Warranty	1-year full coverage 5-year limited

PRO NAILING SYSTEM

FOR NON-STOP NAILING

3

Paslod	P <sup>°</sup> AUGE ANGLED Li-ion Finish Naile	 ess Finish/Trim
	<ul> <li>7.4 V Li-ion battery Drives up to 12,000 nails per charge</li> <li>Cordless Convenience and Mobility Less mess and clutter, no dirty hoses to drag around</li> <li>No-Mar Tip Protects wood from damage</li> <li>Tool-Free Depth of Drive Precise control of nail depth, no tools needed</li> <li>Lightweight and Powerful Easy on the arm, drives 21/2" nails into the hardest woods</li> </ul>	 Fool SpecificationsCordless 16ga. Angled Finish Nailer9024004.6lbs w/battery100 (2 strips)1¼" - 2½"Angled 16ga Smooth, GalvanizedFinish/Trim Fuel (part# 816007)Approx. 1,200Li-ion battery (part# 902654)12,000 nails per charge90-day normal wear parts1-year limited5-year extended limited
IM250S-Li 16 G	AUGE STRAIGHT Li-ion Finish Nation         7.4 V Li-ion battery         Drives up to 12,000 nails per charge         Battery Standby Position         Conserves battery power         Lightweight         Only 4.6 lbs for added comfort and control         Open Line of Sight         Allows for accurate nail placement         No-Mar Tip         Protects premium wood surfaces when nailing         Designed and Assembled in the USA.	 Tool SpecificationsCordless 16ga. Straight Finish Nailer9160004.6lbs w/battery100 (2 strips)1¼" - 2½"Straight 16ga Smooth, GalvanizedFinish/Trim Fuel (part# 816007)Approx. 1,200Li-ion battery (part# 902654)12,000 nails per charge90-day normal wear parts1-year limited5-year extended limited
IM200Li 18 GAU	GE STRAIGHT Li-ion Brad Nailer         7.4V Li-ion Battery         Drives up to 12,000 nails per charge         Lightweight         Only 4.6 lbs, less fatigue and better handling         Battery Standby Position         Conserves battery power         Tool-Free Depth of Drive         Precise control of nail depth, no tools needed         No-Mar Tip         Protects premium wood surfaces when nailing         Designed and Assembled in the USA.	Tool SpecificationsCordless 18ga. Brad Nailer9180004.6lbs w/battery100 (2 strips)5/8" - 2"18ga Smooth, GalvanizedFinish/Trim Fuel (part# 816007)Approx. 1,200Li-ion battery (part# 902654)12,000 nails per charge90-day normal wear parts1-year limited5-year extended limited

Visit **paslode.com** for product reviews, downloads, videos and more Paslode® is a registered trademark of Illinois Toci Works Inc. ©2016

# **Paslode**<sup>®</sup>

Plas

#### 16 GAUGE STAPLER Cordless ½" Crown

Cordless Convenience and Mobility Freedom from hoses or compressors

**Powerful & Lightweight** Drives 2" staples into the hardest woods, less fatigue

**Quick-Clear Feature** Easy access to nose reduces downtime

Floating Tip

For siding over softwall sheathing or  $\operatorname{Celotex}^{\mathbb{R}}$ 

Designed and Assembled in the U.S.A.

#### **Other Cordless**

Tool Specifications				
Model	Cordless 16ga. Stapler			
Part #	900078NT			
Weight	6.3lbs w/battery			
Staple Capacity	150 (2 strips)			
Staple Range	3⁄4" - 2"			
Staple Type	16ga. Standard (½") Crown Galvanized			
Fuel Type Staples per Fuel Cell	Finish/Trim Fuel (part# 816007) Approx. 1,200			
Battery	Ni-Cd stick battery (part# 402500)			
Battery Life	4,000 staples per charge			
Warranty	90-day normal wear parts 1-year limited 5-year extended limited			

#### CORDLESS FUEL, BATTERIES, AND ACCESSORIES

Part #	Product	Description	Associated Product(s)		
816008	All-Season Framing Fuel	1,200 nails; 21-month shelf life	905600 - CF325XP Cordless Framing Nailer 902600 - CF325Li Cordless Framing Nailer		
816007	Finish/Trim Fuel (2-pack)	1,200 nails; 21-month shelf life	902400 - Cordless 16ga. Angled Li-ionFinish Nailer 916000 - Cordless 16ga. Straight Li-ion Finish Nailer 918000 - Cordless 18ga. Li-ion Brad Nailer (coming soon) 900078NT - Cordless 16ga. Stapler (with below adapter)		
902550	Yellow Fuel Adapter		900078NT - Cordless 16ga. Stapler		
902654	Paslode Li-Ion Battery	Framing: 9,000 nails per charge Finish: 12,000 nails per charge Full charge in 90 minutes	905600 - CF325XP Cordless Framing Nailer 902400 - Cordless 16ga. Angled Li-ion Finish Nailer 916000 - Cordless 16ga. Straight Li-ion Finish Nailer 918000 - Cordless 18ga. Li-ion Brad Nailer (coming soon)		
902667	Paslode Li-Ion Battery Charger	2x faster charge time, 2 minute quick charge drives up to 200 nails	902654 Paslode Li-Ion Battery		
219413	Auto Adapter Kit	Charger base and auto adapter cord	All Paslode Li-ion Tools		
402500	Paslode Ni-Cd Stick Battery	2 hour charge; 4,000 staples per charge	900078NT - Cordless 16ga. Stapler		
900200	Paslode Ni-Cd Battery Charger	2 hour charge time	404717 - Oval Battery, 402500 - Stick Battery		
900507	Auto Adapter Charger	Use with 900200 battery charger	900200 - Paslode Battery Charger		
219377	Cordless Li-ion Framing Tune-up Kit		905600 - CF325XP Cordless Framing Nailer 902600 - CF325Li Cordless Framing Nailer		
219409	Cordless Li-ion Finish/Trim Tune-up Kit		902400 - IM250A-Li 16 Gauge Angled Li-ion Finish Nailer 916000 - IM250S-Li 16 Gauge Straight Li-ion Finish Nailer 918000 - IM200Li 18 Gauge Straight Li-ion Brad Nailer		
219348	Cordless Tool Cleaner	12oz. Bottle	All Paslode Cordless tools		
401482	Cordless Nailer Lubrication Oil	4oz. bottle	All Paslode fuel-powered cordless nailers		
902425	No-Mar Tip	1ea - Angled	902400 - Cordless 16ga. Angled Finish Nailer		
912236	No-Mar Tips	3-pack - Straight	916000 - Cordless 16ga. Straight Finish Nailer		
901252	No-Mar Work Contact Element	1-pack - Framing	905600 - CF325XP Cordless Framing Nailer		



#### **Pneumatic Framing**

#### ANNIVERSARY 30° Pneumatic Framing Nailer



Durable	
Rugged design withstands tough	i jobsites
<b>Reliable</b> Consistent performance shot after	er shot

Tool Specifications						
Model	50th Anniversary Framing Nailer					
Part #	511990					
Weight	8.5lbs					
Nail Capacity	84 (2 strips)					
Nail Range	2" - 31⁄2"					
Nail Type	30° Paslod ounDrive® Full Head 30° Paslode Clipped Head					
Operating						
Pressure	80-120 psi (5.5-8.3 bar)					
Warranty	1-year full 5-year extended					



#### **POWERFRAMER TM 30° Pneumatic Framing Nailer** PF350S



**Durable Construction** Requires less maintenance

Powerful Drives nails flush, even in LVL

**Compact Size** Fits between studs

**Adjustable Rafter Hook** Moves out of the way when not in use

**Soft Grip Handle** For maximum comfort

10	or specifications
Model	PF350S PowerFramer
Part #	502000
Weight	7.95lbs
Nail Capacity	84 (2 strips)
Nail Range	2" - 31/2"
Nail Type	30° Paslode RounDrive® Full Head 30° Paslode Clipped Head
Operating	
Pressure	80-120 psi (5.5-8.3 bar)
Warranty	90-day limited on wear parts 6-month limited on magazine parts 1-year limited on housing and cap

Tool Specification

Designed and Assembled in the U.S.A.



#### Positive Placement

**PF250S-PP POSITIVE PLACEMENT**<sup>®</sup> 1<sup>1</sup>/<sub>2</sub>" + 2<sup>1</sup>/<sub>2</sub>" Metal Connector Nailer



#### **Dependable** Drive nails consistently to maximize productivity and efficiency

#### Accurate Probing tip guides nails into hardware holes

**Lightweight and Compact** Reduces fatigue and increases maneuverability

**Quick Release Magazine** Provides access to the nail raceway for faster service times – saves time and money.

Tool Specifications					
Model	PF250S-PP				
Part #	511800				
Weight	7.8lbs				
Nail Capacity	55 (2 strips)				
Nail Range	11/2" + 21/2"				
Nail Type	Positive Placement Metal Connector Nails Smooth (Heat Treated) Brite and Mechanically Galvanized				
Operating	00 100 mi (E.E. 0.0 har)				
Pressure	80-120 psi (5.5-8.3 bar)				
Warranty	90-day limited on wear parts 6-month limited on magazine part 1-year limited on housing and cap				

Designed and Assembled in the U.S.A.

**PF150S-PP POSITIVE PLACEMENT**<sup>®</sup> 1½" Metal Connector Nailer



**Durable** Made for tough jobsite conditions and daily use

Accurate Probing tip guides nails into hardware holes

**Compact** Fits in tight spaces and reduces fatigue

То	ol Specifications
Model	PF150S-PP
Part #	502300
Weight	6.3lbs
Nail Capacity	44-47 (2 strips)
Nail Range	11/2"
Nail Type	Positive Placement Metal Connector Nails Smooth (Heat Treated) Brite and Mechanically Galvanized
Operating Pressure	80-120 psi (5.5-8.3 bar)
Warranty	90-day limited on wear parts 6-month limited on magazine parts 1-year limited on housing and cap

Designed and Assembled in the U.S.A.

<b>Paslod</b>	e	Pneun	matic Finish/Trim
T250A-F16 16 (	GAUGE ANGLED Finish Air Nailer		
	Designed for Precision WorkCleanly sets nails with open line of sightHigh Quality CraftmanshipSmaller 16 gauge nails reduce splitting and nail visibilityCompact & Angled MagazineAble to get into the tightest spotsLightweightEasy on the armDesigned and Assembled in the USA.	Model Part # Weight Nail Capacity Nail Range Nail Type Operating Pressure Warranty	Tool SpecificationsT250A-F165009103.8lbs100 (2 strips)1¼" - 2½"Angled 16ga. Galvanized80-120 psi (5.5-8.3 bar)90-day limited on wear parts, 6 month limited on magazine parts, 1 year limited on housing and cap parts
T250S-F16 16 (	GAUGE STRAIGHT Finish Air Nail	er	
	<ul> <li>Designed for Precision Work</li> <li>Cleanly sets nails with open line of sight</li> <li>High Quality Craftmanship</li> <li>Smaller 16 gauge nails reduce splitting and nail visibility</li> <li>Compact &amp; Straight Magazine</li> <li>Increased installation speed</li> <li>Powerful</li> <li>Drives ¾" - 2½" nails into the hardest woods</li> </ul>	Model Part # Weight Nail Capacity Nail Range Nail Type Operating Pressure Warranty	Tool SpecificationsT250S-F16 $501680$ $3.9lbs$ $100 (2 strips)$ $3/4" - 21/2"$ Straight 16ga. Galvanized80-120 psi (5.5-8.3 bar)90-day limited on wear parts, 6 month limited on magazine parts, 1 year limited on housing and cap parts
T200-F18 18 G/	AUGE Brad Finish Air Nailer		Tool Specifications
	<ul> <li>Prevents Wood Splitting</li> <li>18 gauge brads leaves smaller holes</li> <li>Slender Design</li> <li>Reaches the tightest spots, and provides precision nailing</li> <li>Protects Wood</li> </ul>	Model Part # Weight Nail Capacity Nail Range	18ga. Brad Air Nailer 500959 2.1lbs 100 (2 strips) 5/8" - 2"
	Protects wood No-Mar tip prevents damage to expensive wood	Nail Type Operating Pressure	18ga. Galvanized 90-100 psi (6.2-6.8 bar)

Powerful Drives 5/8" - 2" brads into the hardest woods

5/8" - 2"
18ga. Galvanized
90-100 psi (6.2-6.8 bar)
90-day limited on wear parts,
6 month limited on magazine parts,
1 year limited on housing
and cap parts

Warranty

# **Paslode**<sup>®</sup>

#### CS150 CAPSTAPLER Housewrap Stapling System



**Staples and Caps in One Easy Step** Caps protect against tearing and water damage

**Consistant Drive Performance** Save time on roofing felt and house wrap

Easy Loading Open design makes reloading a snap

Use with FasCaps Combo Pack

#### **Pneumatic Staplers**

T	ool Specifications
Model	CS150
Part #	502575
Weight	4.8lbs
Staple Capacity	90 Staples
Cap Capacity	240 Caps/Spool
Staple Range	1" - 1½"
Staple Type	18ga. 3/8" Narrow Crown
Operating Pressure	70-110 psi (4.8-7.6 bar)
Warranty	90-day, 1-year limited

**Tool Specifications** 

**Tool Specifications** 

#### S200-S16 Framing Stapler



Versatile			
Great for floor	decking, plywood	sheathing, and	insulation

Durable For everyday use and long tool life

**Top Load Magazine** Easy reload and reduced staple waste

**Compact & Lightweight** Increased maneuverability

Model Part # Weight **Staple Capacity** Staple Range Staple Type Operating Pressure Warranty

S200-S16 501230 4.9lbs 150 3⁄4" - 2" 16ga. - Standard Crown (1/2") 80-120 psi (5.5-8.3 bar) 90-day, 1-year limited

#### S200-W16 Insulation Sheathing Stapler



Versatile	1
Drives up to 2" wide crown staples for various applications	

Designed and Assembled in the U.S.A.

**Tool-less Quick Clear Nose** Removes jams easily

**Top Load Magazine** Easy reload and reduced staple waste

**Lightweight & Well Balance** Increased productivity


S200-W16 Model Part # 501265 Weight 4.9lbs **Staple Capacity** 150 Staple Range 3⁄4" - 2" Staple Type 16ga. - Wide Crown (15/16") Operating Pressure 80-120 psi (5.5-8.3 bar) Warranty 90-day, 1-year limited

Designed and Assembled in the U.S.A.



#### Framing Fasteners

#### **FRAMING NAILS** 30° Paper Tape Framing Nails



RounDrive <sup>®</sup> Framing Nails					
Part #	Length	Diameter	Shank	Finish	#/Box
650272	2"	.113"	Smooth	Brite	5,500
650273	2"	.113"	Ring	Brite	5,500
405253	2 1/2"	.131"	Smooth	Brite	3,000
650237	2 3/8"	.113"	Smooth	Brite	5,000
650238	2 3/8"	.113"	Ring	Brite	5,000
650836	3"	.120"	Smooth	Brite	2,500
650830	3"	.131"	Smooth	Brite	2,500
650839	3 1/4"	.131"	Smooth	Brite	2,500
650381	2"	.113"	Ring	HDG Plus	2,000
650382	2 3/8"	.113"	Smooth	HDG Plus	2,000
650383	2 3/8"	.113"	Ring	HDG Plus	2,000
650384	3"	.120"	Smooth	HDG Plus	2,000
650385	3"	.120"	Ring	HDG Plus	2,000
650386	3"	.131"	Smooth	HDG Plus	2,000
650387	3"	.131"	Ring	HDG Plus	2,000
650388	3 1/4"	.131"	Smooth	HDG Plus	2,000
650474	3 1/4"	.131"	Ring	HDG Plus	2,000
650476	3 1/2"	.131"	Smooth	HDG Plus	2,000
For use with 905600, 511990 and 502000					

219228

No-Mar Nose

	Clipped Head Framing Nails							
Part #	Length	Diameter	Shank	Finish	#/Box			
401548	2 1/4"	0.113	Smooth	Brite (Heat Treated)	4,000			
097969	2 3/4"	0.120	Smooth	Brite	3,500			
097970	2 3/4"	0.120	Ring	Brite	3,500			
097973	3"	0.120	Ring	Brite	3,000			
097978	3 1/4"	0.131	Ring	Brite	2,500			
097987	3 1/2"	0.131	Smooth	Brite	2,500			

# (P8d) (P8) (P10) (P10L) (P16)

Positive Placement® Nail heads marked for easy identification

Positive Placement <sup>®</sup> Metal Connector Nails				
Part #	Length	Diameter	Finish	#/box
650645	1 1/2"	.131"	Brite, Heat Treated	1,000
650025	1 1/2"	.131"	Brite, Heat Treated	4,000
650646	1 1/2"	.148"	Brite, Heat Treated	1,000
650026	1 1/2"	.148"	Brite, Heat Treated	3,000
650199	2 1/2"	.131"	Brite, Heat Treated	2,500
650027	2 1/2"	.148"	Brite, Heat Treated	2,500
650028	2 1/2"	.162"	Brite, Heat Treated	2,000
650197	1 1/2"	.131"	Mechanical Galv, Heat Treated	4,000
650481	1 1/2"	.148"	Mechanical Galv, Heat Treated	500
650014	1 1/2"	.148"	Mechanical Galv, Heat Treated	3,000
650106	2 1/2"	.148"	Mechanical Galv, Heat Treated	2,500
650198	2 1/2"	.162"	Mechanical Galv, Heat Treated	2,000
For use v	vith 51180	0, 502300, a	and 500855	

501000 - F350-S PowerMaster Plus

# PNEUMATIC ACCESSORIESPart #ProductDescriptionAssociated Product(s)403720Pneumatic Nailer<br/>Lubrication Oil12oz. bottleAll Paslode pneumatic nailers

Protects wood surfaces



#### Finish/Trim Fasteners

#### RIM NAILS AND STAPLES

16 gauge	16 gauge Angled Trim Nails						
Part #	Length	Gauge	Finish	Quantity			
650230	1 1/4"	16 ga. Angled	Galvanized	2,000			
650231	1 1/2"	16 ga. Angled	Galvanized	2,000			
650046	1 3/4"	16 ga. Angled	Galvanized	2,000			
650047	2"	16 ga. Angled	Galvanized	2,000			
650232	2 1/2"	16 ga. Angled	Galvanized	2,000			

6 boxes per carton, 12,000 Qty

For use with 902400, 900600 and 500910



16 gauge Straight Trim Nails				
Part #	Length	Gauge	Finish	Quantity
650282	11/4"	16 Ga. Straight	Galvanized	2,000
650283	11/2"	16 Ga. Straight	Galvanized	2,000
650284	1 3/4"	16 Ga. Straight	Galvanized	2,000
650285	2"	16 Ga. Straight	Galvanized	2,000
650287	2 1/2"	16 Ga. Straight	Galvanized	2,000

6 boxes per carton, 12,000 Qty

For use with 916000, 902000 and 501680

18 gauge Brad Nails						
Part #	Length	Gauge	Finish	Quantity		
650212	1"	18 Gauge Brad	Galvanized	2,000		
650213	1 1/4"	18 Gauge Brad	Galvanized	2,000		
650214	1 1/2"	18 Gauge Brad	Galvanized	2,000		
650215	2"	18 Gauge Brad	Galvanized	2,000		

6 boxes per carton, 12,000 Qty

For use with 901000, 500959 and 918000

16 gauge Standard (1/2") Crown Staples					
Part #	Length	Wire	Crown	Finish	Quantity
OT5240	3/4"	16 Gauge	1/2"	Galvanized	21,000
0T5242	1"	16 Gauge	1/2"	Galvanized	16,500
OT5243	1 1/8"	16 Gauge	1/2"	Galvanized	15,000
OT5238	1 1/4"	16 Gauge	1/2"	Galvanized	13,500
OT2695	1 1/2"	16 Gauge	1/2"	Galvanized	10,500
OT2250	1 3/4"	16 Gauge	1/2"	Galvanized	9,000
OT2258	2"	16 Gauge	1/2"	Galvanized	7,500
For use with 900078NT and 501230					

16 gauge Wide (15/16") Crown Staples Length Wire Part # Crown Finish Quantity 404068 3/4" 16 Gauge 15/16" Galvanized 9,000 404069 7/8" 15/16" 9,000 16 Gauge Galvanized 404070 1" 16 Gauge 15/16" Galvanized 9,000 404071 1 1/4" 16 Gauge 15/16" Galvanized 9,000 OT2855 1 1/2" 16 Gauge 15/16" Galvanized 10,500 650098 1 3/4" 16 Gauge 9,000 15/16" Galvanized 403471 2" 16 Gauge 15/16" Galvanized 7,500

For use with 501265



FasCap	s Plastic	Caps and		M <b>O</b>	
Part #	Length	Wire	Crown	Finish	Quantity
650592	1"	18 Gauge	3/8"	Galvanized	10,080 Carton
650597	1 1/2"	18 Gauge	3/8"	Galvanized	8,640 Carton

FasCaps are 6 inner boxes per carton For use with 502575

#### Innovation.

Paslode has over 80 years of experience of bringing innovative solutions to the construction industry.

Paslode introduced the first pneumatic nailer, cordless framing nailer, and Positive Placement<sup>®</sup> metal connector system, and has led the way in fastener technology with products like RounDrive<sup>®</sup> 30° papertape collated nails and Hot Dipped Galvanized Plus - the first corrosion-resistant fastener coating for treated lumber.

Today, Paslode's latest innovations include complete fastening systems that consistently improve the user experience and increase jobsite productivity.

#### **Quality.**

Paslode is committed to excellence, and stands by its products. Paslode leverages decades of expertise in tool and nail manufacturing to deliver products that are made under the highest quality standards in the industry.

## **Reputation.**

Paslode is the standard by which other pneumatic and cordless fastening systems are measured. Our products are widely used by professionals for framing, sheathing, trim and finish applications, fencing, floor and roof decking, siding, and insulation.



## **Technical Support**

Email: tech@paslode.com Call: 800.222.6990

3/2016 #50071